


*HOTLINE: +91-8169185739 +91-9594649625

www.crimscent.com



Technical Parameters

| Alarm method: | sound/light/ vibration/display | Sensor life: | 2 years |
|----------------------|-----------------------------------|----------------------------|----------------------|
| Response time: | T ₉₀ <60s | Display: | 2.4 inch LCD display |
| Charging time: | 4~6 hours | Explosion- proof level: | IP65 |
| Working time: | ≮10 hours | Product Size: | 174*68*47mm |
| Working environment: | -20°C~50°C,<95%RH | Weight: | 400g |





K-600 Gas Detector with Built-in Pump

K-600 portable multi-gas detector with built-in pump is a new intelligent gas detector, which adopts an advanced integrated circuit, with standard intelligent level design technology, and proprietary digital analog hybrid communication technology. The detector has excellent sensitivity and repeatability, which makes it very easy to use and maintain. Thus greatly meets the safety requirements of industrial sites with high reliability. The detector is made of high-strength engineering plastics, compound non-slip rubber, which has high strength and good hand feeling. what's more, the detector is water-proof, dust-proof and explosion-proof.

It is widely used in petroleum, chemical, environmental, metallurgy, refining, gas transmission and distribution, biochemical medicine, agricultural and other industries.

Product Features

- (%) Chinese-English switching
- Sound light vibration and display the four alarm methods
- (a) Support PID gas sensor
- (5) Expandable to five gases
- Support multiple gas unit
- (Curve value display



Technical Data

| Detecting gas | Range | Resolution | Low alarm point | High alarm point |
|------------------|--------------|------------|-----------------|------------------|
| EX | 0~100%LEL | 1%LEL | 20%LEL | 50%LEL |
| H ₂ S | 0~100ppm | 1ppm | 10ppm | 35ppm |
| СО | 0~1000ppm | 1ppm | 50ppm | 150ppm |
| O_2 | 0.0~30.0%VOL | 0.1%VOL | 19.5%VOL | 23.5%VOL |





